



Standards for sems Screws



Sr. No.	Machine Screw Size	Shank length	Head Shape	Head Dia	Head Thick	Screw R.M Details	Clamp (Washer), Dimention			Washer R.M Thickness	Washer R.M Grade	Clamp (Washer) Type
							Length	Width	Ht of Washer			
M3 range												
1	M3*0.5.6G	7	Pan Combi	5.0-5.50	2.00 - 2.20	M.S.L.C CHQ	5.90-6.10	5.90-6.10	1.20-1.30	0.9-1.0	M.S. CRC	2
2	M3*0.5.6G	7	Pan Combi	5.0-5.50	2.00 - 2.20	M.S.L.C CHQ	6.40-6.60	6.40-6.80	1.20-1.40	0.9-1.0	M.S. CRC	2
3	M3*0.5.6G	6	Pan Combi	3.80-4.20	1.70 - 2.00	M.S.L.C CHQ	6.40-6.60	4.70-4.90	1.30-1.50	0.9-1.0	M.S. CRC	1
4	M3*0.5.6G	7	CH HD Combi Pozi	5.0-5.50	2.00 - 2.20	Boron Steel 10B21/15B25	6.40-6.60	6.40-6.60	1.30-1.60	1.0-1.20	C-40/C-55	2
5	M3*0.5.6G	7	CH HD Combi Pozi	5.0-5.50	2.30 - 2.50	Boron Steel 10B21/15B25	5.80-6.00	5.50-5.70	1.20-1.40	0.9-1.0	C-55/C-40	1
6	M3*0.5.6G	8.5	CH HD Combi Pozi	5.30-5.60	2.40 - 2.60	Boron Steel 10B21/15B25	7.40-7.60	7.10-7.30	2.20-2.40	1.10-1.20	C-55/C-40	1
M3.5 range												
7	M3.5*6.6 6G	6.5	Pan Combi	5.80-6.20	2.40 - 2.60	M.S.L.C CHQ	6.40-6.60	6.40-6.60	1.70-2.00	1.50-1.60	M.S. CRC	2
8	M3.5*6.6 6G	8	CH HD Combi Pozi	5.80-6.20	2.40 - 2.60	M.S.L.C CHQ	7.60-7.80	7.60-7.80	1.60-1.80	1.10-1.20	M.S. CRC	2
9	M3.5*6.6 6G	9	CH HD Combi Pozi	5.80-6.20	2.40 - 2.60	M.S.L.C CHQ	7.60-7.80	7.60-7.80	1.60-1.80	1.10-1.20	M.S. CRC	2
10	M3.5*6.6 6G	9	CH HD Combi Pozi	5.80-6.00	2.30 - 2.50	Boron Steel 10B21/15B25	7.60-7.80	7.60-7.80	1.60-1.80	1.10-1.20	C-40/C-55	2
11	M3.5*6.6 6G	8.5	Pan Combi	5.80-6.20	2.40 - 2.60	M.S.L.C CHQ	7.90-8.10	6.20-6.40	2.60-2.80	1.30-1.4	M.S. CRC	1
12	M3.5*6.6 6G	7	CH HD Combi	5.80-6.20	2.40 - 2.60	M.S.L.C CHQ	7.40-7.60	7.40-7.60	1.60-1.80	1.10-1.20	M.S. CRC	1
13	M3.5*6.6 6G	8.5/9.0	CH HD Combi	5.80-6.20	2.40 - 2.60	Boron Steel 10B21/15B25	8.50-8.70	8.10-8.30	2.80-3.00	1.50-1.60	C-55/C-40	1
14	M3.5*6.6 6G	9	CH HD Combi Pozi	6.00-6.50	2.40 - 2.60	M.S.L.C CHQ	7.20-7.40	7.30-7.50	2.70-2.80	1.50-1.60	M.S. CRC	1
15	M3.5*6.6 6G	12.5/13.0	CH HD Combi	5.80-6.20	2.40 - 2.60	Boron Steel 10B21/15B25	8.50-8.70	8.10-8.30	2.90-3.00	1.50-1.60	C-55/C-40	1
16	M3.5*6.6 6G	12.5/13.0	CH HD Combi	5.80-6.20	2.40 - 2.60	Boron Steel 10B21/15B25	8.50-8.70	7.40-7.60	3.10-3.20	1.50-1.60	C-55/C-40	1
17	M3.5*6.6 6G	13.5	CH HD Combi	5.80-6.20	2.40 - 2.60	Boron Steel 10B21/15B25	8.50-8.70	8.10-8.30	2.90-3.00	1.50-1.60	C-55/C-40	1
18	M3.5*6.6 6G	9.5	CH HD Combi Pozi	6.30-6.50	2.50 - 2.70	Boron Steel 10B21/15B25	7.40-7.60	7.50-7.70	3.00-3.10	1.50-1.60	C-55/C-40	1
19	M3.5*6.6 6G	8.5	Pan Combi	5.80-6.20	2.40 - 2.60	Boron Steel 10B21/15B25	7.20-7.50	7.40-7.60	2.50-2.60	1.00-1.10	M.C. CRC	1
M4 range												
20	M4*0.7-6G	8	Pan Combi	6.80-7.20	2.40 - 2.60	M.S.L.C CHQ	8.80-9.00	6.80-7.00	1.50-1.60	1.10-1.20	M.S. CRC	1
21	M4*0.7-6G	9	Pan Combi	6.80-7.20	2.80 - 3.00	M.S.L.C CHQ	9.80-10.00	7.50-7.70	2.40-2.50	1.10-1.20	M.S. CRC	1
22	M4*0.7-6G	11.5	CH HD Combi	6.80-7.20	2.90 - 3.00	Boron Steel 10B21/15B25	11.30-11.50	10.30-10.50	2.90-3.00	1.50-1.60	C-55/C-40	1
23	M4*0.7-6G	10	CH HD Slot	6.80-7.20	2.40 - 2.60	M.S.L.C CHQ	10.50-10.60	9.60-9.80	3.40-3.50	1.50-1.600	C-55/C-40	1
24	M4*0.7-6G	12	CH HD Slot	6.80-7.20	2.40 - 2.60	M.S.L.C CHQ	10.50-10.60	9.60-9.80	3.40-3.50	1.50-1.60	C-55/C-40	1
M5 range												
25	M5*0.8 6G	8.5	Pan Combi	8.40-9.90	3.40 - 3.60	M.S.L.C CHQ	11.40-11.60	9.40-9.60	2.30-2.40	1.50-1.60	M.S. CRC	1
26	M5*0.8 6G	12	Pan Combi	9.70-10.50	2.90 - 3.10	M.S.L.C CHQ	14.00-14.30	11.40-11.60	4.10-4.20	1.90-2.00	C-55/C-40	1
27	M5*0.8 6G	17	Pan Slot	9.70-9.90	2.90 - 3.10	M.S.L.C CHQ	14.00-14.30	11.40-11.60	4.10-4.20	1.90-2.00	C-55/C-40	1
28	M5*0.8 6G	12	Pan Combi	8.40-9.00	3.40 - 3.60	M.S.L.C CHQ	11.80-12.00	11.80-12.00	1.90-2.00	1.40-1.50	M.S. CRC	2
M6 range												
29	M6*1.0-6G	14.5	HEX SLOT	10.0-10.20	3.90 - 4.20	M.S.L.C CHQ	14.80-15.20	14.80-15.20	2.70-2.90	1.90-2.00	M.S. CRC	2
30	M6*1.0-6G	12	Pan Combi	10.00-10.50	3.90 - 4.20	M.S.L.C CHQ	14.80-15.20	14.80-15.20	2.70-2.90	1.90-2.00	M.S. CRC	2